



GL-Z45

Base	Voltage(v)	Lifetime(h)	C.T.	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E27	110-240	25000	2700-6500K	≥ 80	3	360	250 ± 10%
Ambient Temperature		Dimension(mm)	Measurement(mm)	G.W.(kgs)	PCS/carton		
-20°C ≥ 40°C		Φ45 × 45 × 78	540 × 280 × 220	5.6	100		



GL-Q45

Base	Voltage(v)	Lifetime(h)	C.T.	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E27	110-240	25000	2700-6500K	≥ 80	3	360	250 ± 10%
Ambient Temperature		Dimension(mm)	Measurement(mm)	G.W.(kgs)	PCS/carton		
-20°C ≥ 40°C		Φ45 × 45 × 78	540 × 280 × 220	5.6	100		



GL-M45

Base	Voltage(v)	Lifetime(h)	C.T.	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E27	110-240	25000	2700-6500K	≥ 80	3	360	250 ± 10%
Ambient Temperature		Dimension(mm)	Measurement(mm)	G.W.(kgs)	PCS/carton		
-20°C ≥ 40°C		Φ45 × 45 × 78	540 × 280 × 220	5.6	100		

LED Ceramic Bulb



GL-G45



Base	Voltage(v)	Lifetime(h)	C.T.(K)	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E14	110-240	25000	2700-6500	≥ 80	3	220	250 ± 10%
Ambient Temperature		Dimension(mm)		Measurement(mm)		G.W.(kgs)	PCS/carton
-20°C ≥ 40°C		Φ45 × 45 × 80		540 × 280 × 220		6.7	100

Base	Voltage(v)	Lifetime(h)	C.T.(K)	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E27	110-240	25000	2700-6500	≥ 80	3	220	250 ± 10%
Ambient Temperature		Dimension(mm)		Measurement(mm)		G.W.(kgs)	PCS/carton
-20°C ≥ 40°C		Φ45 × 45 × 76		540 × 280 × 205		6.75	100



GL-CG60

Base	Voltage(v)	Lifetime(h)	C.T.(K)	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E27	110-240	25000	2700-6500	≥ 80	5	220	450 ± 10%
Ambient Temperature		Dimension(mm)		Measurement(mm)		G.W.(kgs)	PCS/carton
-20°C ≥ 40°C		Φ60 × 60 × 110		380 × 360 × 265		6	50

LED LAMPS

High Light Efficiency
80% Energy-Saving Long Lifetime



GL-C37-TIP



GL-C37

Base	Voltage(v)	Lifetime(h)	C.T.(K)	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E27/E14	110-240	25000	2700-6500	≥ 80	3	220	250 ± 10%
Ambient Temperature	Dimension(mm)	Measurement(mm)	G.W.(kgs)	PCS/carton			
-20°C ≥ 40°C	Φ37 × 37 × 126	500 × 260 × 305	6.8	100			

Base	Voltage(v)	Lifetime(h)	C.T.(K)	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E27/E14	110-240	25000	2700-6500	≥ 80	3	220	250 ± 10%
Ambient Temperature	Dimension(mm)	Measurement(mm)	G.W.(kgs)	PCS/carton			
-20°C ≥ 40°C	Φ37 × 37 × 103	500 × 260 × 275	6.6	100			

LED Ceramic Bulb



GL-G50

Base	Voltage(v)	Lifetime(h)	C.T.(K)	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E27	110-240	25000	2700-6500	≥ 80	5	220	450 ± 10%
Ambient Temperature		Dimension(mm)	Measurement(mm)	G.W.(kgs)	PCS/carton		
-20°C ≥ 40°C		φ50 × 50 × 80	540 × 280 × 205	8.5	100		



GL-P45

Base	Voltage(v)	Lifetime(h)	C.T.(K)	CRI	Wattage	Beam Angle(Degree)	Lumen Flux(lm)
E27	110-240	25000	2700-6500	≥ 80	3	360	220 ± 10%
Ambient Temperature		Dimension(mm)	Measurement(mm)	G.W.(kgs)	PCS/carton		
-20°C ≥ 40°C		φ54.5 × 45 × 78	540 × 280 × 220	5.6	100		